

Geometrie- und Anbaumaße RCC.06

FRAME						
	Geometrie	XS	S	M	L	XL
	A [mm]	420	450	480	510	540
	B [mm]	545	565	585	605	625
	C [°]	71				
	D [°]	74	73,5	73,5	73	72,5
	E [mm]	425				
	F [mm]	1030	1045	1065	1080	1095
	G [mm]	-				
	H [mm]	300				
	I [mm]	705	730	755	775	795
ANBAUMASSE	Steuerrohrlänge	XS	S	M	L	XL
		95 mm	105 mm	110 mm	125 mm	135 mm
	Gewicht Rahmen	1.600 Gramm				
	Innenlager [BSA 68 mm]	XT BB-ES70, BSA 68/73-113 mm		XTR BB-M952, BSA 68/73-113 mm		
	Sattelstütze	27,2 mm				
FEDERGABEL	Umwerfer	XT FD-M751, 31.8 mm Top Swing, Top Route		XTR FD-M953, 31.8 mm Top Swing, Top Route		
	Empfohlener Federweg 80 mm Keine Doppelbrückengabel zugelassen					
	ROCK SHOX Duke SL 80 mm ROCK SHOX PSYLO XC 80 mm		Einbaulänge / Offset 451/39 mm			
	MAGURA O ₂ u 80 mm		Einbaulänge / Offset 459/39,5 mm			